



Notes:

1. Model 930 uses D1 and D2 rated 25 amp.
2. Model 940 used D1 and D2 rated 50 amp.
3. Model 950 may use D1 and D2 rated 50 amp or D1-D4 rated 25 amp.
4. C1 - 10 mfd 660 VAC
5. C2, C3- (if used) rated .47 mfd 250 volt (optional component)
6. TS3- may be used on UL model and must be used on -2 models.
7. TS4- Thermal one-shot, integral part of transformer, not field serviceable.

REV	CHANGE	DATE	DWN BY	<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES;</p> <p>TOLERANCES X/X=P1/64 .XXX=P.005 .XX=P.01 =POD 30'</p> <p>THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PARALLAX POWER COMPONENTS, LLC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS PARALLAX MAY OTHERWISE AGREE IN WRITING.</p>
A	RELEASED	02/27/02	Martin W. Redd	
			DES.ENG. Martin W. Redd	
			QUALITY MFG.ENG. RELSE	
<p>TITLE</p> <p>900 SERIES MODEL 930,940,950</p>				
SIZE	THIRD ANGLE PROJECTION	DWG NO.	900 Series Model 930,940,950	
SCALE	None		SHEET	Sheet 1 of 1